# 8-Gallon | Two Stage Gasoline

Increase your productivity by merging two vital pieces of equipment into one versatile machine. Ideal for every industrial application requiring both air and electrical power, you'll save space and save money with this machine.





AMERICAN SPRAY TECHNOLOGIES
AUBURN, WA (877) 833-4342

# **Compressor Pump**

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

#### Generator

- Brushless alternator
- Total harmonic distortion (THD) less than 5%
- 100% copper windings
- Comes standard with (2) 120V, 20A and (1) 240V, 20A receptacles

## Frame

- Powder coated 8-gallon twin tank receivers
- $^{3}\!\!/_{16}$ -inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- 13-inch flat-free tires

### **Components**

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 12 or 16 1/2-inch fly wheel
- Quality pilot valve unloader

**Portable Model** 

**AG2-PK14-08M1** 16.4

Model Number



Compressor

AG2-PK14-08M1

Displacement/Engine

429cc Kohler CH440 OHV



Dimensions (LxWxH)

52x28x34in.



Ship Wt. Net Wt.

375 lb.

450 lb.

\*Equipped with 150-PSI maximum rated regulator

CFM @

90 PSI CFM @ PSI

| Accessories & Options: |  |               |
|------------------------|--|---------------|
| Part Number            | Description  | Fits Model    |
| 70-0358                | Engine oil drain extension - 14-inch flexible drain hose makes oil changes clean and easy                                    | AG2-PK14-08M1 |
| 854-0093               | Service truck mount kit (recommended for mounted service truck applications) - Includes four rubber isolators to reduce wear | AG2-PK14-08M1 |
| AW-6000-1002           | Equipment cover - Keeps your equipment clean, dry and looking like new   | AG2-PK14-08M1 |
| AX-0028                | Lifting hook - For easier portability  | AG2-PK14-08M1 |
| AX-0071                | Electric start - battery, box and cables not included - For easy starting  | AG2-PK14-08M1 |
| AX-0072*               | Electric start - battery box and cables included, battery not included - For easy starting                                   | AG2-PK14-08M1 |

\*Battery box cannot be mounted at the factory but can be shipped with the unit for custom mounting. Consult factory for more information.

Alternator Wattage
| Cont. With | C

Comp.

Max. Output On-Load

15.7 @ 175\* 4000 watts | 2300 watts

Cont. With

Comp.

Off-Load

Receptacles

3500 watts (2) NEMA 5-20R, (1) NEMA L6-20R